



Cold food counters - Freshness at a glance

Fresh salads, colourfully filled baguettes or cooled starters become appealing eye catchers in the cool food counters by Bartscher. Also drinks and snacks are well presented in the high-quality refrigerated showcases.

In the serving business and at meal counters the guests can directly access the cooled products or ask to have handed over the fresh snacks of their choice. The refrigerating showcases offer everything necessary for the practical use: convection cooling, an automatic defrost function and flexibly insertable support grates. The cold food counters with double pane are energy-efficient, provide stability and a good view of the good presented - and suitably put in the limelight thanks to the energy-saving LED lighting.



Refrigerated display "Bartscher Deli-Cool I"

Show-case with 3 shelves and interior lighting. The refrigerated display is equipped with sliding doors on operation side.

- ✓ Model: interior and exterior plastic
- ✓ Ventilated cooling
- ✓ Temperature range: 2 °C to 12 °C
- ✓ Interior LED lighting



Refrigerated display "Bartscher Deli-Cool I"

Automatic defrost
 Capacity: 100 litres
 Coolant: R600a
 Power: 0,16 kW / 230 V 50 Hz
 Size: W 685 x D 455 x H 675 mm
 2 height adjustable grids,
 dimensions: W 600 x D 300 mm
 Weight: 40,5 kg
 GTIN 4015613479101
Code-No. 700201G



Refrigerated displays "Bartscher Deli-Cool"

Show-case with 3 shelves and interior lighting

The refrigerated displays are equipped with sliding doors on operation side.

- ✓ Design: Plastic casing with double glass panel, safety glass
- ✓ Circulation cooling with 2 ventilators
- ✓ Temperature range: 2 °C to 12 °C
- ✓ Interior LED lighting

Refrigerated display "Bartscher Deli-Cool II"

Automatic defrost

Capacity: 120 litres

Coolant: R600a

Power: 0,16 kW / 230 V 50 Hz

Size: W 710 x D 575 x H 685 mm

2 height adjustable grids,
dimensions: W 635 x D 340 mm, W 635 x D 370 mm

Weight: 57 kg

GTIN 4015613505558

Code-No. 700202G



Refrigerated display "Bartscher Deli-Cool II D" with 2 sliding doors at the front and back and therefore operable from both sides

Automatic defrost

Capacity: 120 litres

Coolant: R600a

Power: 0,16 kW / 230 V 50 Hz

Size: W 710 x D 568 x H 686 mm

2 height adjustable grids,
dimensions: W 630 x D 340 mm, W 630 x D 370 mm

Weight: 55 kg

GTIN 4015613617688

Code-No 700208G



Refrigerated display "Bartscher Deli-Cool III"

Automatic defrost

Capacity: 160 litres

Coolant: R600a

Power: 0,16 kW / 230 V 50 Hz

Size: W 885 x D 575 x H 685 mm

2 height adjustable grids,
dimensions: W 810 x D 370 mm, W 810 x D 400 mm

Weight: 68,4 kg

GTIN 4015613505565

Code-No. 700203G





Cooling display 67L with 8 GN containers 1/6 GN

Stainless steel casing
Glass lid, safety glass
For 1 x 1/1 GN and 1 x 1/3 GN, GN-Containers 100 mm deep
Cutting board made of polyethylene
Static cooling
Automatic defrost
Capacity: 67 litres
Temperature range: 0 °C to 10 °C
Coolant R600a
Power: 0,07 kW / 230 V 50 Hz
Size: W 765 x D 610 x H 320 mm
Includes:
3 adaptor bars: length 360 mm, width 30 mm
8 GN containers 1/6 GN, 100 mm deep, CNS 18/10
Weight: 27,6 kg
GTIN 4015613625294
Code-No. 700211G



Refrigerated display 40L

Top mounted display for the self-service area - ideal for cold drinks, yoghurts or snacks that need cool storage such as sandwiches, etc.
Stainless steel casing with safety glass
Static cooling
Automatic defrost
Capacity: 40 litres
Temperature range: 0 °C to 12 °C
Coolant R600a
Display area: stainless steel baseplate, removable,
W 645 x D 300 mm, usable height 260 mm
Power: 0,105 kW / 230 V 50 Hz
Size: W 670 x D 575 x H 335 mm
Weight: 26,6 kg
GTIN 4015613625300
Code-No. 700212G



Refrigerated display "Buffet"

Plastic casing with safety glass
Operation side with sliding doors
LED lighting
Ventilated cooling
Automatic defrost with drip water evaporation
Capacity: 154 litres
Temperature range: 2 °C to 6 °C
Coolant R600a
Display area made of stainless steel, W 900 x D 285 mm
1 intermediate shelf made of glass, W 925 x D 250 mm
Maximum inner height:
bottom 205 mm, top 175 mm
Power: 0,14 kW / 230 V 50 Hz
Size: W 1050 x D 645 x H 640 mm
Weight: 61 kg
GTIN 4015613586670
Code-No. 700206G

Base unit

Varnished steel panel
4 swivel castors (2 with brakes)
Size: W 834 x D 607 x H 570 mm
Weight: 10 kg
GTIN 4015613617824
Code-No. 700209





Set the stage for sweet temptations - cake displays for a strong presentation

Delicious cream cakes, juicy apple pies or tender-melting chocolate tarts - the sight alone is delectable! The finishing touch is achieved with the appealing presentation of the fine pastries. With the cake displays units from Bartscher, your sweet bakery products will be eye-catchers - fresh and cool, guaranteed!

Depending on the model, up to six cakes can be exhibited impressively, one above the other. Of course, the glazed cooling units are also suited for the appetising presentation of snacks and other foods.

Double-glazed and equipped with LED illumination, ventilated cooling and an automatic defrosting system, these display units are particularly well-suited for permanent operation and are easy to clean and care for.



Cake display show-case 72L

For the perfect presentation of tarts, cakes or cold snacks. The rotating stand ensures an eye-catching display of your food.

Model: plastic housing with all-round double glass panel

1 door, hinged on the right

LED lighting, individually switchable

Forced-air cooling with 2 fans

Automatic defrost function

Capacity: 72 litres

Temperature range: 2 °C to 10 °C

Coolant R600a

Electronic control, digital display

Humidity: max. 70 %

Rotating stand:

- Individually switchable

- Automatic turning stop when opening of the door

- With 4 welded shelves, Ø 315 mm, distance between the shelves: 160 mm

- Can be removed for easy cleaning

Power: 0,17 kW / 230 V 50 Hz

Size: Ø 450 mm, height 983 mm

Weight: 39 kg

GTIN 4015613586687

Code-No. 700207G



Ample space to present tarts, cakes or snacks

- ✓ 6 intermediate shelves made of glass, Ø 530 mm, height adjustable
- ✓ Rotatable intermediate shelves
- Easy replenishment and release of food

Cake display show-case 400L

Thanks to the diameter of 530 mm the 6 stable 5 mm thick glass shelves offer ample space to present tarts, cakes or snacks effectively.

Stainless steel base

Plastic housing with all-round double glass panel, safety glass

1 door, hinged on the right

LED lighting, individually switchable

Forced-air cooling with 1 fan

Automatic defrost function with drip water evaporation

Capacity: 400 litres

Temperature range: 2 °C to 10 °C

Coolant R134a

Electronic control, digital display

Humidity: max. 75 %

6 height adjustable, rotatable intermediate shelves made of glass, Ø 530 mm, can be removed for easy cleaning

5 swivel castors, 2 with brakes

Power: 0,48 kW / 220-240 V 50 Hz

Size: Ø 680 mm, height 1750 mm

Weight: 131 kg

GTIN 4015613652061

Code-No. 700214



Display fridge KV 270L

Ideal for presenting chilled snacks or cakes in an appealing design.

Model: stainless steel casing with all-round glazing, double safety glass

Operation side with sliding doors

LED lighting, individually switchable

Forced air cooling

Automatic defrost function

Condensation water evaporation

Capacity: 270 litres

Temperature range: 2 °C to 8 °C

Coolant R134a

Storage space made of glass, W 840 x D 360 mm

2 height adjustable intermediate shelves made of glass, size:

W 800 x D 370 mm, W 800 x D 360 mm

4 castors, 2 with brakes

Power: 0,475 kW / 220-240 V 50 Hz

Size: W 913 x D 680 x H 1245 mm

Weight: 126 kg

GTIN 4015613615431

Code-No. 700551



- ✓ Operation side with sliding doors





Multideck refrigerated display case "Rimi"

Stainless steel finish
Stainless steel front panel, glazed side panels
LED lighting
Capacity: 220 litres
3 shelves, W 465 x D 280 mm
Distance between shelves 230 mm
Bottom shelf size: W 465 x D 340 mm
Display area: 0,52 m²
Ventilated cooling
Climate class 6
Coolant R404a
Automatic defrosting
Temperature range: 2 °C to 10 °C
4 castors with 2 brakes
Power: 1,34 kW / 230 V 50 Hz
Size: W 494 x D 600 x H 1742 mm
Night blind included
Weight: 106 kg
GTIN 4015613505282
Code-No. 700220

Multideck refrigerated display case 390L

Model: plastic housing with double-glazed panel
Interior: lacquered sheet steel
LED lighting
Capacity: 390 litres
3 height-adjustable shelves with price rails
- top size: W 842 x D 300 mm
- centred, bottomed size: W 842 x D 352 mm
Bottom shelf size: W 876 x D 558 mm
Display area: 1,24 m²
Ventilated cooling
Climate class 6
Coolant R404a
Automatic defrosting
Temperature range: 2 °C to 10 °C
4 castors, 2 separate brakes
Power: 1,4 kW / 220-240 V 50 Hz
Size: W 925 x D 850 x H 1515 mm
Night blind included
Weight: 127 kg
GTIN 4015613641607



Display fridge Bartscher Panorama 550L

Ideal for presenting goods in a professional way. Whether you have drinks, yoghurts, sweet or savoury snacks - your goods can be perfectly stocked in this display with high visibility from all sides.

Stainless steel
All-round glazing, 3-fold glazing
1 door, hinged on the right
LED lighting
Capacity: 550 litres
Ventilated cooling
Coolant R134a
Automatic defrost function
Temperature range: 0 °C to 6 °C
4 castors, 2 with brakes
Power: 0,65 kW / 230 V 50 Hz
Size: W 850 x D 650 x H 1900 mm
3 grids, chrome-plated metal, height-adjustable
Weight: 189,5 kg
GTIN 4015613610740
Code-No. 700550



Mini Cooler 58L

With interior light
Volume: 58 litres
Ventilated cooling
Coolant: R600a
Automatic defrost
Temperature range: 2 °C to 12 °C
On/Off switch
Power: 0,18 kW / 230 V 50 Hz
Size: W 425 x D 380 x H 805 mm
Including 2 height adjustable grids
Weight: 28,5 kg
GTIN 4015613635057

Code-No. 700258G



Mini Cooler 78L

With interior light
Volume: 78 litres
Ventilated cooling
Coolant: R600a
Automatic defrost
Temperature range: 2 °C to 12 °C
On/Off switch
Power: 0,18 kW / 230 V 50 Hz
Size: W 425 x D 380 x H 960 mm
Including 3 height adjustable grids
Weight: 32,5 kg

Mini Cooler 78L, white

GTIN 4015613635071

Code-No. 700578G

Mini Cooler 78L, black

GTIN 4015613635088

Code-No. 700277G



Mini Cooler 78L in stainless steel

Chrome nickel steel
With LED lighting
Volume: 78 litres
Ventilated cooling
Coolant: R600a
Automatic defrost
Temperature range: 2 °C to 12 °C
4 height adjustable feet
On/Off switch
Power: 0,18 kW / 230 V 50 Hz
Size: W 430 x D 390 x H 986 mm
Including 3 height adjustable grids, chromed
Weight: 41,8 kg
GTIN 4015613633466

Code-No. 700478G



Mini Cooler Slim-Line 80L

With LED lighting
 Volume: 80 litres
 Ventilated cooling
 Coolant: R600a
 Automatic defrost
 Temperature range: 2 °C to 12 °C
 On/Off switch
 Power: 0,18 kW / 230 V 50 Hz
 Size: W 375 x D 385 x H 1050 mm
 Including 4 height adjustable grids
 Weight: 36,2 kg
 GTIN 4015613633480

Code-No. 700280G



Mini-Cooler 86L

Two curved doors offer a stocking from front and backside.
 With interior light
 Volume: 86 litres
 Ventilated cooling
 Coolant: R600a
 Automatic defrost
 Temperature range: 2 °C to 12 °C
 On/Off switch
 Power: 0,18 kW / 230 V 50 Hz
 Size: W 425 x D 435 x H 980 mm
 Including 3 height adjustable grids
 Weight: 36,5 kg
 GTIN 4015613635101

Code-No. 700678G



Mini Cooler 98L

With interior light
 Volume: 98 litres
 Ventilated cooling
 Coolant: R600a
 Automatic defrost
 Temperature range: 2 °C to 12 °C
 On/Off switch
 Power: 0,18 kW / 230 V 50 Hz
 Size: W 425 x D 380 x H 1100 mm
 Including 4 height adjustable grids
 Weight: 37,5 kg
 GTIN 4015613635118

Code-No. 700298G



Display fridge 235L

With LED lighting (front side)
 Volume: 235 litres
 Ventilated cooling
 Coolant: R600a
 Automatic defrost
 Temperature range: 2 °C to 12 °C
 4 swivel castors (2 with brakes)
 On/Off switch
 Power: 0,25 kW / 230 V 50 Hz
 Size: W 520 x D 485 x H 1700 mm
 Including 4 height adjustable grids
 Weight: 77 kg
 GTIN 4015613635125

Code-No. 700335G





Refrigerator "Mini"*

Compact refrigerator for mobile use, also in vehicles.

Plastic housing

Volume: 19 litres

Thermoelectric cooling

Cooling capacity: 15 °C to 18 °C below ambient temperature

Lighting

Power: AC 230 V / DC 12 V / 0,056 kW

Size: W 330 x D 370 x H 460 mm

12 V adapter cord included

Weight: 7,3 kg

GTIN 4015613589596

Code-No. 700089

*The device is not suitable for continuous commercial use.



Bottle Cooler 88L

with modern LED lighting and double glass door in a noble design.

Volume: 28 bottles / 88 litres

Adjustable temperature control

Static cooling

Coolant R600a

Temperature range: 2 °C to 10 °C

Energy-saving LED ceiling lighting separately switchable

Door hinged on the right, reversible

2 height-adjustable front feet

Power: 0,085 kW / 220-240 V 50 Hz

(LED lighting 0,8 W)

Size: W 430 x D 480 x H 825 mm

Including 5 chrome-plated bottle racks and
1 chrome-plated rack, removable individually

Weight: 23,4 kg

GTIN 4015613546032

Code-No. 700082G



Bottle Cooler 220L

Interior stainless steel, exterior steel casing finish, painted

Doors double vitrification

Lockable, internal light

Net volume 220 litres

Ventilated cooling

Continuous mechanical temperature control

Temperature range: 2 °C to 10 °C

Power: 0,25 kW / 230 V 50 Hz

Size: W 920 x D 550 x H 920 mm

With 2 grids made of stainless steel

Weight: 82,2 kg

GTIN 4015613528816

Code-No. 110138



Bottle Cooler 270LN

Interior white, exterior white
 Changeable door hinge
 Net volume 267 litres
 Static cooling
 Automatic defrost
 Coolant R600a
 Temperature range: 0 °C to 8 °C
 Internal light with on/off switch
 Evaporator at the back panel
 Energy efficiency category: A+
 Power: 0,12 kW / 230 V 50 Hz 1 NAC
 Size: W 600 x D 620 x H 1450 mm
 5 shelves (4 adjustable)
 Weight: 52 kg
 GTIN 4015613585819

Code-No. 700272



Bottle Cooler 320LN

Interior white, exterior white
 Glass-door with aluminum frame, changeable door hinge
 Net volume 320 litres
 Static cooling
 Automatic defrost
 Coolant R600a
 Temperature range: 0 °C to 10 °C
 Internal light with on/off switch
 Evaporator at the back panel
 Power: 0,23 kW / 230 V 50 Hz 1 NAC
 Size: W 600 x D 600 x H 1730 mm
 5 adjustable shelves
 Weight: 67 kg
 GTIN 4015613523767

Code-No. 700321



Refrigerator 590LW

Material: exterior lacquered steel, interior ABS plastic
 Colour: white
 Capacity: 590 litres
 Forced-air cooling
 Digital control
 Automatic defrost function
 Coolant R600a
 Temperature range: 0 °C to 8 °C
 For ambient temperatures up to max. 30 °C
 Climate class: 4
 On/Off switch with indicator light
 Door self-closing, lockable
 Changeable door hinge
 Height adjustable feet
 Power: 0,26 kW / 220-240 V 50 Hz
 Size: W 735 x D 770 x H 1910 mm
 Includes: 4 height adjustable trays 2/1 GN
 made of steel, plastic coated
 Weight: 101 kg
 GTIN 4015613649474

Code-No. 700800

